



Description

- Rated temperature: 70°C
- Rated voltage: 0.6/1.0KV (Inclusion 300/500V, 450/750V)
- Reference standard: DIN 0281, EN 50525
- Conductor: Soft-annealed tinned or bare copper wire
- Insulation: polrvinyl chloride (PVC)
- Shield: Optional
- Jacket: polrvinyl chloride (PVC)

说明

- 额定温度：70°C
- 额定电压：0.6/1.0KV以下(包含300/500V、450/750V)
- 参考标准：DIN 0281, EN 50525
- 导体类型：退火软镀锡或裸圆铜线
- 绝缘材料：聚氯乙烯 (PVC)
- 屏蔽：可选择是否屏蔽
- 护套材料：聚氯乙烯 (PVC)

Application

For fixed occasions such as indoor ,cable chute,Pipeline and where anti-interference is required Etc.(2-40CORES 0.5-2.5 mm², 2-12CORES 4-70 mm²)

应用

用于控制、监控联锁回路及保护线路等场所，安装在室内、移动要求柔软的场所(2-40芯 0.5-2.5 mm²， 2-12芯 4-70 mm²)

| NO. 编号 | CORE 芯数 | Conductor 导体 | | Insulation 绝缘 | | Jacket 护套 | | Max. Resistance at 20°C 最大导体电阻 (Ω/km) | Re. weight 参考重量 (Kg/Km) |
|---------|---------|--------------------------------|-------------------|---------------|-------------------|---------------|-------------------|---------------------------------------|-------------------------|
| | | Section 截面积 (mm ²) | Structure 结构 (mm) | Thick 厚度 (mm) | Nom. dia. 外径 (mm) | Thick 厚度 (mm) | Nom. dia. 外径 (mm) | | |
| JZ05050 | 2 | 0.5 | 28/0.15 | 0.6 | 2.15±0.15 | 0.8 | 7.5±0.25 | 39.0 | 88 |
| JZ10075 | 10 | 0.75 | 42/0.15 | 0.6 | 2.35±0.15 | 1.2 | 12.0±0.60 | 26.0 | 225 |
| JZ16150 | 16 | 1.5 | 48/0.20 | 0.7 | 3.05±0.15 | 1.2 | 16.1±0.80 | 13.3 | 454.2 |
| JZ04A00 | 4 | 10 | 140/0.30 | 1.0 | 6.6±0.15 | 1.8 | 20.0±0.80 | 1.91 | 710.8 |
| JZ04B50 | 4 | 25 | 196/0.40 | 1.2 | 10.0±0.25 | 2.0 | 28.5±1.50 | 0.780 | 1611.3 |
| JZ07A00 | 7 | 10 | 140/0.30 | 1.0 | 6.6±0.25 | 2.0 | 24.5±1.00 | 1.91 | 1227.5 |